

## M282

## UWT Universal Wear Tester

Universal Wear Tester. Determines the wear and abrasion resistance of fabrics used in clothing, footwear and industrials.

Redesigned UWT features digital controls for accurate cycle counting and timing, improved air injection system for more uniform inflation of the diaphragm used in surface abrasion testing, and a superior clamping mechanism for repeatable specimen tensioning.

Tests are run in automatic mode to obtain definite results of high reproducibility and to lessen the need for operator evaluation of test results. The digital counter either counts the number of cycles to specimen rupture or can be preset for automatic shutoff without specimen failure. The user can select the timer mode for accurate countdown of test time while simultaneously counting the number of abrasion cycles.

Supplied with surface abrasion head (inflated diaphragm method and flex abrasion head), tension and head weights and initial supply of abrasives. Fitted with built-in timer and mechanical cycle counter. Repeatable and reproducible testing is ensured by consistent motor speed providing 120 double strokes per minute of 25 mm(1in) stroke length. Accessories are available for conducting frosting, pilling and edge abrasion tests.

Pilling tests utilize a special elastomeric pad attached to the specimen holder of the optional Frosting Attachment. The specimen is rubbed with a second elastomeric pad mounted on the upper head as the abradant.

Edge and fold abrasion tests expose the seam edge or fold of the specimen to the abradant by mounting the specimen in the optional Edge and Fold Abrasion Clamp.



<b>WEIGHT</b>	102 kg	225 lb	
<b>DIMENSIONS</b>	Width	Depth	Height
	330 mm	500 mm	460 mm
	13 inch	19.5 inch	18 inch
<b>STANDARDS</b>	<b>FTMS 191,5300,5302</b>	<b>AATCC 119,120</b>	
<b>FORD EFB 15J2/BN 112-01</b>	<b>ASTM D3514,D3885,D3886</b>		

### ORDERING INFORMATION

M282	Universal Wear Tester
M282A	Frosting Attachment
M282B	Edge and Fold Abrasion Clamp
M282C	Abradent "0" 50 yd roll
M282D	Abradent "600A" 50 yd roll
M282E	Abradent "320J" 50 yd roll
M282F	Elastometric Friction Pad, Base Pad and Preparation Fabric for ASTM D 3514
M282G	3 sets of 5 Photographic Standards for ASTM D 3514

#### SDL Atlas, Ltd

PO Box 162, Crown Royal, Shawcross St., Stockport SK1 3JW,  
Tel: +44 (0) 161 480 8485 Fax: +44 (0) 161 480 8580  
Internet: <http://www.sdlatlas.com>

#### SDL Atlas, LLC

3934 Airway Drive, Rock Hill, SC 29732, USA  
Tel: +1 (803) 329-2110 Fax: +1 (803) 329-2133  
Internet: <http://www.sdlatlas.com>

#### SDL Atlas, Ltd

1/F (South-East) & 2F, Shenjian Mansion, Central District (West), Hi-Tech Park, Nanshan, Shenzhen, 518057, P.R.C.  
Tel: +86 (755) 2671 1168 Fax: +86 (755) 2671 1337  
Internet: <http://www.sdlatlas.com.cn>

#### SDL Atlas, Ltd

3J, Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong  
Tel: (852) 2173 8611 Fax: (852) 2370 2949  
Internet: <http://www.sdlatlas.com>